

D5200



At the heart of the image



I AM ALL YOUR IDEAS

EXPEED 3

NIKKOR

HDMI
HIGH-DEFINITION MULTIMEDIA INTERFACE



**SD
XC**

Explore your creativity with the D5200's versatile swivel monitor: flip it, tilt it, turn it to capture unique shots. Share your best images straight to your iOS and Android smartphone or tablet*.



*This feature requires use of the optional Wireless Mobile Adapter WU-1a, sold separately

Introducing the creative camera with a twist. Whether you're out exploring or celebrating that special occasion, you can see everything from your own unique perspective in astonishing detail and share your best shots with friends and family.

I AM THE BEAUTY OF LIFE

If you love to see things in glorious detail, then the 24.1-megapixel CMOS sensor will do all your shots justice. The 39-point Auto Focus System works with you to capture the world in razor-sharp detail. The Scene Recognition System works alongside the 2016-pixel metering sensor to optimize exposure, Auto Focus and white balance so you can capture crisply defined images.



I AM YOUR CREATIVE TWIST

The versatile swivel monitor gives you endless creative freedom so you can experiment with every shot. Go further than just photography. Full HD movie capability with built-in stereo microphone means you can get cinematic quality video any time.



I AM NOT ALONE

Love to share your photos? With the Wireless Mobile Adapter you can share stunning quality shots straight to compatible smartphones or tablets*. You can also use it to shoot and preview images remotely, or get a great shot from the trickiest of angles when you're out and about.

*This feature requires use of the optional Wireless Mobile Adapter WU-1a, sold separately



At the heart of the image

CHOOSE YOUR ACCESSORIES



WU-1A WIRELESS ADAPTER

Enables sharing straight to compatible smartphones or tablets*



AF-S DX NIKKOR 35mm f/1.8G

Ideal for portraits, gives a soft background blur



AF-S DX NIKKOR 18-300mm F3.5-5.6G ED VR

All-in-one high power super zoom



NIKON SB-700 SPEEDLIGHT


Expertly manages the direction and quality of light



*Sold separately



Focus	
Lens servo	• Auto Focus (AF): Single-servo AF (AF-S); continuous-servo AF (AF-C); auto AF-S/AF-C selection (AF-A); predictive focus tracking activated automatically according to subject status • Manual focus (MF): Electronic rangefinder can be used
Focus point	Can be selected from 39 or 11 focus points
AF-area mode	Single-point AF; 9-, 21-, or 39- point dynamic-area AF; 3D-tracking, auto-area AF
Flash	
Built-in flash	Auto, portrait, child, close up, night portrait, party/indoor, pet portrait, color sketch: Auto flash with auto pop-up P, S, A, M, H flood: Manual pop-up with button release
Guide Number	Approx. 12/39, 13/43 with manual flash (m/ft., ISO 100, 20°C/68°F)
Flash control	TTL: i-TTL flash control using 2016-pixel RGB sensor is available with built-in flash and SB-910, SB-900, SB-800, SB-800, SB-600, or SB-400; i-TTL balanced fill-flash for digital SLR is used with matrix and center-weighted metering, standard i-TTL flash for digital SLR with spot metering
White balance	
White balance	Auto, incandescent, fluorescent (7 types), direct sunlight, flash, cloudy, shade, preset manual, all except preset manual with fine-tuning
Live View	
Lens servo	Auto Focus (AF): Single-servo AF (AF-S); full-time-servo AF (AF-F)
AF-area mode	Face-priority AF, wide-area AF, normal-area AF, subject-tracking AF
Auto Focus	Contrast-detect AF anywhere in frame (camera selects focus point automatically when face-priority AF or subject-tracking AF is selected)
Automatic scene selection	Available in auto and auto (flash off) modes
Movie	
Frame size (pixels) and frame rate	• 1,920 x 1,080, 60i (59.94 fields/s)/ 50i (50 fields/s)*, ★ high/normal • 1920 x 1080, 30p (progressive)/25p/24p, ★ high/normal • 1280 x 720, 60p/50p, ★ high/normal • 640 x 424, 30p/25p, ★ high/normal
File format	MOV
Audio recording device	Built-in or external stereo microphone; sensitivity adjustable
Monitor	
Monitor	7.5-cm (3-in.), approx. 921k-dot (VGA), var-angle TFT monitor with 170°; viewing angle, approx. 100% frame coverage, and brightness adjustment
Power source	
Battery	One rechargeable Li-ion EN-EL14 battery
Dimensions/weight	
Dimensions (W x H x D)	Approx. 129.0 x 98.0 x 78.0 mm (5.1 x 3.9 x 3.1 in.)
Weight	Approx. 555 g (1 lb 3.6 oz) with battery and memory card but without body cap; approx. 505 g/1 lb 1.8 oz (camera body only)
Supplied accessories	
Supplied accessories	EN-EL14 rechargeable Li-ion battery (with terminal cover), MH-24 battery charger, AN-DC3 strap, UC-E17 USB cable, EG-CP16 audio/video cable, DK-5 eyepiece cap, BS-1 accessory shoe cover, DK-20 rubber eyecup, BF-1B body cap, ViewNX 2 CD-ROM, User's Manual



*Supplied accessories **Non-Nikon products