

Pro8500

Brilliant and 3D-Ready

High Brightness and Networkable

The ViewSonic® Pro8500 is an advanced high brightness DLP® installation projector which includes BrilliantColor™ technology to produce more vibrant colors. The Pro8500 delivers 5000 lumens with a 1024x768 XGA native resolution, allowing it to shine in virtually any lighting situation. The Pro8500 provides maximum mounting flexibility with a wide 1.5X optical zoom adjustment and a multitude of connectivity options including Network Display, USB, and WiFi. The filter-less design and long lamp life provide for easy maintenance and low total cost of ownership.



Network control through RJ-45

Schedule, manage and monitor the projector remotely and receive e-mail alerts of projector lamp status.

Closed captioning

Integrated closed captioning decoder for the hearing impaired.

HDMI 1.3

Through HDMI 1.3 and a full array of other input interfaces provide all the connectivity needed.

PC-Less Slide Show Presentation

Project your pictures or images directly from a USB flash drive without a PC.

Bright in virtually any setting with 5,000 lumens

Ultra-bright 5,000 lumen output makes this the perfect choice for large boardrooms, conference halls and auditoriums.

Give Greener presentations and save

Use the Eco mode to achieve lower power consumption, reduce overall noise and extend lamp life.

USB Display

Project your presentations through any USB connection without the hassle of running a bulky VGA cable.

Network Display

With its advanced management software, you can project up to 4 PCs at the same time with the ability of broadcast up to 8 projectors.

BrilliantColor™ technology

Latest BrilliantColor technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The sophisticated 6-segment color wheel enhances the yellow color performance that is key to accurate and vivid color reproduction.

Stay connected

Supports multiple video timing formats from SD (NTSC, PAL & SECAM) to HD 1080p.

Wireless Capability

Allow the projector to be WiFi enabled with an optional USB wireless adapter(WPD-100)

ViewSonic®
See the difference™ 

Pro8500

Networkable High Brightness Projector - 120Hz and 3D-ready



Optional Accessories

- Replacement Lamp RLC-059
- Wireless Presentation Gateway..... WPG-360
- USB Wireless Adapter..... WPD-100

| Projection Distance | | 4:3 Aspect | | | |
|---------------------|------|------------|--------|------|--------|
| | | Wide | | Tele | |
| M | Feet | M | Inches | M | Inches |
| 1.0 | 3.28 | 0.86 | 33.9 | 0.57 | 22.4 |
| 1.5 | 4.92 | 1.29 | 50.8 | 0.86 | 33.9 |
| 2.0 | 6.56 | 1.72 | 67.7 | 1.15 | 45.3 |
| 3.0 | 9.84 | 2.59 | 102 | 1.75 | 67.7 |
| 5.0 | 16.4 | 4.31 | 169.7 | 2.87 | 113.0 |
| 10.0 | 32.8 | 8.62 | 339.7 | 5.74 | 226.0 |



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

| Model Name | Pro8500 | |
|---------------------|-----------------------------|--|
| Display | Type | 0.7" Digital Micromirror Device (DLP™) |
| | Resolution | XGA 1024 x 768 (Native) |
| | Lens | 1.5x Manual optical zoom / Manual optical focus |
| | Keystone | Vertical digital keystone correction: +/- 40 degrees |
| | Size | 30" - 300" / 0.76m - 7.6m |
| | Throw Distance | 1.2m - 10m / 3.9ft - 32.8ft |
| | Throw Ratio | 1.45 - 2.18:1 |
| | Lamp | 280 watt |
| | Lamp Life (Normal/Eco-mode) | 4000 / 5000* hours |
| | Brightness | 5000 Lumens |
| | Contrast Ratio | 4900:1 (dynamic) |
| | Aspect Ratio | 4:3 (Native), 16:9, 16:10, (Auto) |
| | Input Signal | Computer And Video |
| Frequency | | Fh: 31 - 100KHz, Fv: 48 - 120Hz |
| Compatibility | | PC Mac |
| Connector | RGB Input | VGA to UXGA VGA to SXGA+ |
| | RGB Output | VGA to UXGA |
| | Digital Input | 15-pin mini D-sub (x2) |
| | Component | 15-pin mini D-sub |
| | Composite Input | HDMI 1.3 |
| | S-video Input | RCA (x3) |
| | USB | 4-pin mini - DIN |
| | Microphone | Type A: for PC-less slide show presentation-support JPEG, BMP, TIFF, PNG, GIF from USB flash drive, optional wireless USB adapter. Mini-B: for direct presentation from PC. (not Mac compatible) |
| | Audio Input | 3.5mm mini mon jack |
| | Audio Output | 3.5mm mini jack |
| Audio Power | Control | RS-232 (8 Pin Mini - Din) |
| | Network | RJ45 |
| Controls | Speaker | 10W (x2) |
| | Voltage | 90~240VAC (Auto Switching), 50/60Hz (universal) |
| Operating Condition | Power Consumption | 350W (typ) / <1W (stand-by mode) |
| | Basic | Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, auto, mode/enter, source |
| | OSD | Picture: Brightness, Contrast, Colour Setting, Keystone, Aspect Ratio, Image, White Intensity, Gamma, 3D Sync, 3D Sync invert Computer Image: Frequency, Tracking, H Position, V Position Video Image: Saturation, Sharpnes, Tint Setting: Manual Position, Projection, Signal Type, Lamp Hour, Lamp Hour Reset, Filter Mode, Filter Hours, Filter Hours Reset, Power Saving, Auto Source, Eco-mode, High Altitude, OSD Timeout Advance: Blank Screen, Password Word, Screen Capture, Start up Screen, Text Shot, Digital Zoom, DCR, Close Captions, Brilliant colour Network: Wired LAN, Wireless LAN, Network Restart |
| | Temperature | 32°F - 104°F (0°C - 40°C) |
| | Humidity | 10% - 80% (non-condensing) |
| | Altitude | 0~6,000 ft (1,800m), operational up to 10,000 ft (3048m) |
| | Noise Level | 32dB / 27dB |
| | Dimensions (W X H X D) | 13.1 x 4.8 x 10.4 (in) / 333x 122 x 269 (mm) 16.3 x 7.5 x 14.8 (in) / 414 x 190.5 x 375.9 (mm) |
| | Weight | 8.5 lb (3.86 kg) 11.8 lb (5.36 kg) |
| | Regulations | CB, RoHS, SVHC, WEEE, UL/cUL, FCC-B, ICES-004, TUV-S (Argentina), NOM, PSB, C-tick, KC, CE, GOST-R, Hygienic, UKrSEPRO, CCC |
| | | Packing Contents |

For more product information, visit us at www.viewsoniceurope.com

